


Panasonic ideas for life

Boost Your Business Efficiency with an A3-Size Compatible, High-Speed, **Fast-Feeding Scanner**


The fast 90-ppm* scan speed and 200-page ADF (Automatic Document Feeder) of the KV-S5055C make it ideal for both large-volume scanning and dispersed input. ToughFeed, Panasonic's unique paper feed mechanism, also minimizes the possibility of damaging important documents and ensures precise feeding to



ToughFeed Innovative Paper Feed Mechanism

Preventing Damage to the Scanning Glass Stapled Document Detection


Multiple sensors are used to detect various types of stapled documents, and to immediately stop the scanner when stapling is detected. This minimizes damage to both the document and the optical glass.




Staples are quickly detected in any location, to minimize damage to the optical glass and the document.

Accurate Scanning Ultrasonic Double-Feed Detection

The KV-S5055C is equipped with an ultrasonic sensor, which accurately detects double-feeding even when scanning documents of various thicknesses. When detected, the ultrasonic sensor prevents double-feeding by immediately stopping the scanning process.






The sensor detect double-feeding and stops the scanner immediately.

The high-performance sensor catches even subtle changes

Precise Feeding Superior Roller Mechanisms

The paper feed rollers separate from the paper each time a sheet is fed, so the tendency to double-feed caused by the paper feed roller pressure is reduced, even when feeding paper of different thicknesses. Any paper sliding is also detected and the double feed prevention roller pressure is adjusted to prevent the paper from slipping and jamming.



Double Feed Skip (DFS) Key NEW

Should a scan operation stop due to the detection of double-feeding, simply press the DFS key to resume scanning. This is convenient when you don't want scanning to stop due to documents with things like receipts or sticky notes attached, or envelopes.






Self Cleaning Functions


Ionizer NEW

The ion-filled breeze created by the ionizer neutralizes the electrical charge on the documents to be scanned, and reduces the amount of paper dust that clings to their surface. This ion-filled breeze also flows through the paper path and removes paper dust from the scanning glass to reduce the need for the user to clean the glass.



Scanning Glass Cleaning Brush NEW

The brush directly cleans the scanning glass to further prevent paper dust. This eliminates the need for maintenance and ensures comfortable scanning operations.



High-Reliability Scanning

Accurately Feeds Various Sized Documents

Mixed Document Feeding

Documents with different sizes and thicknesses can all be fed together. They can be set in center, left, or right alignment. By using left or right single-side alignment, there is no more need to spend time organizing documents according to their size, so scanning is fast and easy. This function greatly increases work efficiency.







The scanner feeds accurately, regardless of alignment

High-Speed Scanning of Sheets up to 100 feet Long

Long Paper Mode

The highly reliable paper feed mechanism quickly and stably scans long documents. This function boosts work efficiency by smoothly scanning long documents like continuous business forms or electrocardiograms.



Optional Flatbed Scanner

Easily Scan Documents and Booklets

Single User Interface


By selectively using the KV-S5055C and the optional KV-SS080,* you can easily scan documents and booklets, and save them in the same document.

 $^{*}\text{To}$ operate the KV-SS080, the KV-S5055C is required. The KV-SS080 does not operate as a standalone unit.

Save Time by Reducing the Number of Scans **Multi-Crop**

Place various sized documents on the flatbed and scan them all at once, then crop whatever parts you need. This is convenient for scanning multiple business cards and thick documents.





High-Quality Image Processing

Image Capture Plus NEW

Image Capture Plus is an application that transfers image data scanned by a Panasonic high-speed document scanner to a PC in the form of an image file. This software lets you edit scanned pages (switch pages, delete pages, etc.) intuitively using thumbnail images. It also allows you to make various settings to facilitate complex scanning processes and serves as a powerful tool for efficiently processing routine business work, such as filing.

Job setting lets you sort files and folders on a group by group basis, and save the images into them.



Easy Maintenance

The clamshell design allows full, easy access to the entire paper path, so you can clear paper jams, clean the unit, or replace a roller easily without having to call a service technician.



High-Volume ADF

The ADF (Automatic Document Feeder) holds up to 200 sheets of paper to allow continuous scanning of large document runs.



KV-S5055C Specifications

Scanning Face				Duplex
Scanning Method				3-line Color CCD
				Selectable black and white background reference
Scanning Speed *1	*1	Binary / Color	Simplex	Up to 75 ppm (Portrait)
		Letter size		Up to 90 ppm (Landscape)
		200 dpi	Duplex	Up to 150 ipm (Portrait)
		·		Up to 180 ipm (Landscape)
		Binary / Color	Simplex	Up to 50 ppm (Portrait)
		Letter size		Up to 60 ppm (Landscape)
		300 dpi	Duplex	Up to 100 ipm (Portrait)
				Up to 120 ipm (Landscape)
Resolution				600 dpi Optical Resolution 100 - 600 dpi (1 dpi step)
Detection				Ultrasonic double feed detection (1 position),
				Stapled document detection
Compression				JPEG (color, grayscale)
Image Output				Binary, Grayscale (8 bit), Color,
inago Suipui				MultiStream™ output
Binary Mode Halftone				Dither, Error diffusion
Image Control	.0110			Dynamic Threshold, Automatic De-skewing, Automatic Crop,
Executed by driver software or				Automatic Binary/ Color Distinction, Blank Page Removal,
Panasonic Image Capture Plus				Double Exposure, Multi Color Dropout, Smooth Background,
Other Functions				Hole Removal, Border Removal, Noise Reduction,
				Detect File Separation Sheet and much more
				Length control, Barcode detection (ISIS), Patch code detection,
				Automatic separation, Control sheet, Long paper mode
				12.01 in, x 100 in, (305 mm x 2,540 mm)
Scanning Size Documents *2		Size (ADF)	Minimum	1.9 in. × 2.75 in. (48 mm × 70 mm)
Documents 2		Size (ADF)	Maximum	11.7 in. × 2.75 in. (48 mm × 70 mm)
		Marielea	IVIAXIIIIUIII	
		Weight		5 - 42 lbs. (20 - 157 g/m²)
		Thickness		1.6 - 7.9 mils (0.04 - 0.2 mm)
				Note: 1 mil = 0.001 in.
Hopper Capacity				Up to 200 sheets (75 g/m², 20 lbs.) New paper
Supported Operating System				Windows® XP, Windows Vista®, Windows® 7
Interface				USB 2.0
Power Requirement				AC 100 - 240 V, 50/60 Hz
Power		Maximum (Scanning)		1.0 A (100 - 120 V), 0.5 A (220 - 240 V)
Consumption		Minimum (Standby)		0.4 A (100 - 120 V), 0.2 A (220 - 240 V)
		Sleep mode		3.5 W or less (100 - 120 V, 220 - 240 V)
- 1		Temperature		59 °F - 86 °F (15 °C - 30 °C)
Environment		Humidity		20 - 80 % RH
Storage		Temperature		32 °F - 104 °F (0 °C - 40 °C)
Environment Humidity			10 - 80 % RH	
	External Dimensions *3 (W x D x H)			18.5 in. x 17.5 in. x 13.4 in.
External Dimensi				(468 mm x 444 mm x 339 mm)
External Dimensi Weight *3				40 lbs. (18 kg)
Weight *3				40 lbs. (18 kg) CD ROM: Device driver, Operation manual, Installation manual, Control data sheet, Image Capture Plus capture software, ISIS®/TWAIN driver software, User utility software,
Weight *3	Roller	exchange kit		40 lbs. (18 kg) CD ROM: Device driver, Operation manual, Installation manual, Control data sheet, Image Capture Plus capture software, ISIS®/TWAIN driver software, User utility software, Quick Scan Pro (DEMO) Installation manual, Power cord,
Weight *3 Accessories		exchange kit eleaning paper		40 lbs. (18 kg) CD ROM: Device driver, Operation manual, Installation manual, Control data sheet, Image Capture Plus capture software, ISIS®/TWAIN driver software, User utility software, Quick Scan Pro (DEMO) Installation manual, Power cord, Roller cleaning paper, Shading paper, USB cable (2.4 m) & Blower
Weight *3 Accessories	Roller o			40 lbs. (18 kg) CD ROM: Device driver, Operation manual, Installation manual, Control data sheet, Image Capture Plus capture software, ISIS®/TWAIN driver software, User utility software, Quick Scan Pro (DEMO) Installation manual, Power cord, Roller cleaning paper, Shading paper, USB cable (2.4 m) & Blower KV-SS033 KV-SS03
Weight *3 Accessories	Roller o	cleaning paper er unit (Pre)		40 lbs. (18 kg) CD ROM: Device driver, Operation manual, Installation manual, Control data sheet, Image Capture Plus capture software, ISIS®/ TWAIN driver software, User utility software, Quick Scan Pro (DEMO) Installation manual, Power cord, Roller cleaning paper, Shading paper, USB cable (2.4 m) & Blower KV-SS039

Optional Flatbed Scanner KV-SS080 Specifications

•		
Scanning Type		Flatbed
Scanning Method		CCD
Scanning Resolution		100 - 600 dpi (1 dpi step)
Scanning Speed*1 Letter size 2	200 dpi	3.3 sec. (Binary and Color)
Paper Size		Maximum 8.5 in. x 11.7 in. (216 mm x 297 mm)
Interface		USB 2.0
Power Requirement		AC 100 - 240 V, 50/60 Hz
Power Consumption	Scanning	0.35 A (100 - 120 V), 0.2 A (200 - 240 V)
	Standby	0.25 A (100 - 120 V), 0.15 A (200 - 240 V)
	Sleep mode	3.5 W or less (100 - 120 V, 200 - 240 V)
Operating	Temperature	59 °F - 86 °F (15 °C - 30 °C)
Environment	Humidity	30 - 80 % RH
Storage	Temperature	32 °F - 95 °F (0 °C - 35 °C)
Environment	Humidity	10 - 80 % RH
Dimensions*3 (W x D x H)		11.3 in. x 20.4 in. x 3.3 in. (287 mm x 518 mm x 83.5 mm)
Weight*3		7.5 lbs. (3.4 kg)
Accessories		CD-ROM: Operating manual
		AC adaptor, Power cord, USB cable

- The scanning speed differs depending on the host computer, operating system, application, image data amount, and paper type.
 "Weight in pounds" of paper represents the weight of 500 sheets (17 in. x 22 in. / 432 mm x 559 mm).
 Dimensions and weights are approximate.

Dimensions

KV-S5055C KV-SS080 3.3 in. 20.4 in. 17.5 in





















As an ENERGY STAR® Partner, Panasonic has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

Windows® and Windows Vista® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ENERGY STAR® and the ENERGY STAR certification marks are registered US marks.

ISIS® and Quick Scan are registered trademarks or trademarks of EMC Corporation in the United States and other countries.

All other brand or product names are the property of their respective holders. Design and specifications are subject to change without notice.

Panasonic

Panasonic System Networks Company of America